


ТРЪБИ ЗА ГАЗ PIPES FOR GAS SUPPLY

ТРЪБИ ОТ PE 100 PIPES PE 100



БДС EN 1555

Ном. No Nom. No	D mm	e, mm	ТЕГЛО WEIGHT kg/m
SDR 17,6; PN 6 bar; C=2			
4710600201	20	2.3	0.132
4710600251	25	2.3	0.170
4710600321	32	2.3	0.222
4710600401	40	2.3	0.283
4710600501	50	2.9	0.438
4710600631	63	3.6	0.686
4710600751	75	4.3	0.976
4710600901	90	5.2	1.413
4710601101	110	6.3	2.086
4710601251	125*	7.1	2.673
4710601401	140*	8.0	3.351
4710601601	160*	9.1	4.374
4710601801	180*	10.3	5.556
4710602001	200*	11.4	6.827
4710602251	225*	12.8	8.607
4710602501	250*	14.2	10.626
4710602801	280*	15.9	13.292
4710603151	315*	17.9	16.828
4710603551	355*	20.2	21.426
4710604001	400*	22.8	27.202
SDR 11; PN 10 bar; C=2			
4711000201	20	3.0	0.162
4711000251	25	3.0	0.210
4711000321	32	3.0	0.278
4711000401	40	3.7	0.429
4711000501	50	4.6	0.666
4711000631	63	5.8	1.054
4711000751	75	6.8	1.472
4711000901	90	8.2	2.132
4711001101	110	10.0	3.163
4711001251	125 *	11.4	4.103
4711001401	140 *	12.7	5.114
4711001601	160 *	14.6	6.713
4711001801	180 *	16.4	8.485
4711002001	200 *	18.2	10.464
4711002251	225 *	20.5	13.244
4711002501	250 *	22.7	16.289
4711002801	280 *	25.4	20.421
4711003151	315 *	28.6	25.850
4711003551	355 *	32.3	32.899
4711004001	400 *	36.4	41.759

*Прави тръби до 12 m

*Length of straight pipes up to 12 m.

C е коефициент на сигурност, съгласно посочения стандарт.


C is a value of safety according to indicated standard.



ТРЪБИ ЗА ГАЗ PIPES FOR GAS SUPPLY

ТРЪБИ ОТ PE 80
PIPES PE 80

БДС EN 1555



Ном. No Nom, No	D mm	e _n mm	ТЕГЛО WEIGHT kg/m
SDR 17,6; PN 4,8 bar; C=2			
4720480201	20	2,3	0,132
4720480251	25	2,3	0,170
4720480321	32	2,3	0,222
4720480401	40	2,3	0,283
4720480501	50	2,9	0,438
4720480631	63	3,6	0,686
4720480751	75	4,3	0,976
4720480901	90	5,2	1,413
4720481101	110	6,3	2,086
4720481251	125*	7,1	2,673
4720481401	140*	8,0	3,351
4720481601	160*	9,1	4,374
4720481801	180*	10,3	5,556
4720482001	200*	11,4	6,827
4720482251	225*	12,8	8,607
4720482501	250*	14,2	10,626
4720482801	280*	15,9	13,292
4720483151	315*	17,9	16,828
4720483551	355*	20,2	21,426
4720484001	400*	22,8	27,202
SDR 11; PN 8 bar; C=2			
4720800201	20	3,0	0,162
4720800251	25	3,0	0,210
4720800321	32	3,0	0,278
4720800401	40	3,7	0,429
4720800501	50	4,6	0,666
4720800631	63	5,8	1,054
4720800751	75	6,8	1,472
4720800901	90	8,2	2,132
4720801101	110	10,0	3,163
4720801251	125*	11,4	4,103
4720801401	140*	12,7	5,114
4720801601	160*	14,6	6,713
4720801801	180*	16,4	8,485
4720802001	200*	18,2	10,464
4720802251	225*	20,5	13,244
4720802501	250*	22,7	16,289
4720802801	280*	25,4	20,421
4720803151	315*	28,6	25,850
4720803551	355*	32,3	32,899
4720804001	400*	36,4	41,759

*Прави тръби до 12 m

*Length of straight pipes up to 12 m.

"C" е коефициент на сигурност, съгласно посочения стандарт.

"C" is a value of safety according to indicated standard.

